

**GUJARAT TECHNOLOGICAL UNIVERSITY****BE - SEMESTER-III (NEW) EXAMINATION – SUMMER 2019****Subject Code: 2131404****Date: 11/06/2019****Subject Name: Food Engineering Thermodynamics****Time: 02:30 PM TO 05:00 PM****Total Marks: 70****Instructions:**

1. Attempt all questions.
2. Make suitable assumptions wherever necessary.
3. Figures to the right indicate full marks.
4. Standard Steam Tables and normal range Psychrometric Chart can be used

- Q.1 (a)** Why do gases deviate from ideal behaviour? Ten kilogram of CH<sub>4</sub> is injected into a 110 liter vessel containing oxygen at 2 bar absolute pressure and 13 °C. Calculate the partial pressure of methane gas and the total pressure in the container in kPa assuming isothermal process. **03**
- (b)** Write down Van *der* Waal's equation of state for real gases. Hundred kg of N<sub>2</sub> gas is stored in a 100 liter closed container at – 23 °C. Calculate the pressure of the gas in kPa using Van *der* Waal's gas equation. Take  $a = 0.137 \text{ Pa (m}^3/\text{mole)}^2$ ,  $b = 3.86 \times 10^{-5} \text{ m}^3/\text{mole}$ ,  $R = 8.314 \text{ J/mole K}$  **04**
- (c)** Answer the following: **07**
- (i) State law of corresponding states.
  - (ii) If vacuum is 600 torr, calculate absolute pressure in kPa.
  - (iii) Write SI unit and dimensions of universal gas constant.
  - (iv) Calculate the specific gas constant of O<sub>2</sub> gas.
  - (v) Differentiate between cyclic and reversible process with an example.
  - (vi) Define ideal gas.
  - (vii) Show that  $C_p - C_v = \bar{R}$  for ideal gases.
- Q.2 (a)** Explain Zero<sup>th</sup> law of thermodynamics. List various types of thermometers and briefly explain the working principle constant volume type of thermometer. **03**
- (b)** Define flow work. Steam is steadily flowing through a turbine with inlet and outlet conditions given as: **04**
- INLET CONDITION  
 $h_1 = 3250 \text{ kJ/kg}$ ,  $v_1 = 0.07 \text{ m}^3/\text{kg}$ ,  $P_1 = 60 \text{ bar}$ ,  $t_1 = 550 \text{ °C}$   
 OUTLET CONDITION  
 $h_2 = 3230 \text{ kJ/kg}$ ,  $v_2 = 0.08 \text{ m}^3/\text{kg}$ ,  $P_2 = 50 \text{ bar}$ ,  $t_2 = 480 \text{ °C}$   
 The heat loss due to poor body insulation is 16 kJ/kg. Calculate the steam inlet and outlet velocities in m/s and steam flow rate in kg/s. Assume that turbine inlet and outlet points are at the same elevation.
- (c)** Explain first law of thermodynamics. Prove that  $PV^\gamma = \text{Constant}$  for an ideal gas undergoing a reversible adiabatic process. The temperature of 10 kg of a gas held in a rigid cylinder was increased from 5 °C to 25 °C by adding 55 kJ of heat. Calculate the work done and the change in internal energy of the system. **07**
- [ $C_v = 742 \text{ J/kg K}$ ]
- OR**
- (c)** Define control volume. Derive SFEE for a stream of fluid entering and leaving a nozzle in terms of work and energy transfer per unit mass and state the assumptions made. **07**

**Q.3 (a)** For a 2-phase Liquid-Vapour system in thermal equilibrium, prove that: **03**

$$\ln\left(\frac{P_2}{P_1}\right) = \frac{h_{fg}}{R} \left[ \frac{1}{T_1} - \frac{1}{T_2} \right].$$

**(b)** Explain different types of thermodynamic equilibria and state their conditions of stability. **04**

**(c)** Explain Joule-Kelvin effect. Prove that for a gas undergoing a throttling process, the Joule-Kelvin coefficient is given by **07**

$$\mu_{j,T} = \frac{1}{C_P} \left[ T \left( \frac{\partial v}{\partial T} \right)_P - v \right]$$

**Q.3 (a)** Define entropy. A refrigerator is operating between  $-5^\circ\text{C}$  and  $35^\circ\text{C}$  at a COP of 60% of the maximum possible COP. If the refrigeration effect is 5TR, calculate the power requirement and the heat it has to reject to the ambient. **03**

**(b)** What is Gibb's phase rule? **04**

(i) Calculate the maximum number of phases in which a 2- component mixture can exist in equilibrium with each other.

(ii) Calculate the degrees of freedom of water at its triple point.

**(c)** Show that for any reversible thermodynamic process: **07**

(i)  $\left( \frac{\partial T}{\partial P} \right)_S = \left( \frac{\partial V}{\partial S} \right)_P$

(iii)  $\left( \frac{\partial P}{\partial V} \right)_T \left( \frac{\partial V}{\partial T} \right)_P \left( \frac{\partial T}{\partial P} \right)_V = -1$

(ii)  $(\Delta s)_{1-2} \geq \int_1^2 \left( \frac{dQ}{T} \right)$ .

**Q.4 (a)** Explain the following: (i) Carnot cycle (ii) Thermal reservoirs **03**

**(b)** Explain Carnot theorems. A heat engine is operating between two constant temperature reservoirs at 650 K and 270 K. The engine produces a net steady work output of 10 HP. If the thermal efficiency of the engine is 60% of the Carnot efficiency, calculate heat input to the engine and heat rejection in kW. **04**

**(c)** Explain Kelvin-Planck and Clausius statements of second law of thermodynamics. A heat engine produces 100 kW of power when operating between two thermal reservoirs maintained at  $700^\circ\text{C}$  and  $70^\circ\text{C}$ . The thermal efficiency of the engine is 50% of the maximum possible. Determine **07**

(i) The engine efficiency.

(ii) Rate of heat input to the engine.

(iii) Heat rejected.

**Q.4 (a)** Explain the following in related perspective: **03**

(i) Clausius inequality

(ii) Available and unavailable energy

- (b) Explain the following: 04  
 (i) Second law of thermodynamics (ii) PMM1 And PMM2
- (c) Explain the operation of heat engine, refrigerator and heat pump with the help of schematic diagrams. A refrigerator is operating between source and sink maintained at 0°C and 40°C and respectively. The heat extracted from the source is 5 kW and the heat rejected to the sink is 60% more than what the system absorbs. Calculate the power requirement and COP of the device. What is the ratio of actual COP to the maximum possible COP? 07
- Q.5** (a) Define relative humidity. Prove that specific humidity of moist air is given by 03
- $$\omega = 0.622 \left( \frac{p_w}{p_o - p_w} \right).$$
- (b) Air at a certain place having a barometric pressure of 755 torr has a temperature of 25 °C. If the partial vapour pressure of water vapours present in unsaturated air is 24 mm Hg, calculate the following: 04  
 (i) Specific humidity  
 (ii) Specific enthalpy  
 (iii) Relative humidity  
 (iv) Dew point temperature
- (c) Explain phase diagram of water on a P-V diagram showing various states. 07  
 Define and indicate the location of triple point.  
 Using standard Steam Tables determine the following for saturated steam at 200 °C:  
 (i) Saturation pressure in kPa  
 (ii) Entropy in kJ/kg K  
 (iii) Enthalpy of saturated steam in kJ/kg  
 (iv) Specific volume m<sup>3</sup>/kg
- Q.5** (a) Define the following in relation to moist air: 03  
 (i) Wet bulb temperature  
 (ii) Specific humidity  
 (iii) Dehumidification
- (b) The weather report of Anand city on a summer day is recorded as: Atmospheric air temperature = is 42 °C 04  
 WBT of air = 27 °C  
 Atmospheric pressure = 760 mm Hg.  
 Find out absolute humidity, enthalpy, relative humidity and dew point temperature.
- (c) Explain the following for water/steam: 07  
 (i) Superheated steam (ii) Critical temperature (iii) Sub-cooled water  
 A rigid vessel contains 100 kg saturated steam (x = 1) at a pressure of 8 bar.  
 Calculate the following for using Steam Tables:  
 (i) Density in kg/m<sup>3</sup> (ii) Enthalpy in kJ  
 (iii) Internal energy in kJ (v) Entropy in kJ/K

\*\*\*\*\*